

COMPRESSION TEST OF BUILT-UP
C SECTION COLD-FORMED STEEL
WITH OPENINGS

MOHAMAD NABIL BIN MOHAMED

B. ENG(HONS.) CIVIL ENGINEERING

UNIVERSITI MALAYSIA PAHANG



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : MOHAMAD NABIL BIN MOHAMED

ID Number : AA14241

Date : 31TH MAY 2019

COMPRESSION TEST OF BUILT-UP
C SECTION COLD-FORMED STEEL
WITH OPENINGS

MOHAMAD NABIL BIN MOHAMED

Thesis submitted in fulfillment of the requirements
for the award of the
B. Eng (Hons.) Civil Engineering

Faculty of Civil Engineering and Earth Resources
UNIVERSITI MALAYSIA PAHANG

MAY 2019

ACKNOWLEDGEMENTS

First and foremost, praises to Allah swt, for his showers of blessings through my strength, health, patience and knowledge to complete my final year project successfully. I am grateful and would like to express my sincere gratitude to my supervisor, Mr Khalimi Johan bin Abd Hamid for his germinal ideas and invaluable guidance. His consistent motivations help me to complete my final year project either in laboratory work or writing thesis.

I also would like to show my gratitude to my panels, Mr Ir Dr Fadzil bin Mat Yahaya and Mr Dr Mohd Faizal bin Md Jaafar to their valuable suggestion and beneficial comments on my studies as it allow me to look for more information and extra knowledge in this studies and also the recommendation for future references regarding to this study especially for the juniors.

Moreover, I want to say thanks to all FKASA technical staff who help me in completing my laboratory and all my friends for their support and help during this studies work especially the laboratory work. The journey is made easy with all of you by my side and I will always remember that. All these memories we shared in completing our project and through our fourth year studies in university will always be something that I will treasure for life.

Not forget to my beloved family especially my mother and father who always supporting me all the time with their motivation, encouragement and their prayer day by day throughout all time while studying here at Universiti Malaysia Pahang.

Thank you very much.

ABSTRAK

Kajian ini bertujuan untuk menentukan beban muktamad bagi bahagian C yang terbina terbentuk sejuk dengan bukaan berbanding dengan bahagian C tunggal dan mengkaji tingkah laku lengkokan mod kegagalan bahagian C yang terbina. Keluli terbentuk sejuk digunakan secara meluas dalam industri pembinaan, teknologi pembuatan dan piawaian yang berkaitan. Keluli terbentuk sejuk boleh didapati secara meluas dengan perbezaan saiz dan bentuk. Bahagian keluli terbentuk sejuk dibuat dengan proses yang berbeza seperti pembentukan gulung sejuk dan operasi tekan brek. Dalam ujian mampatan, pemuat mampatan telah dikenakan pada lajur pendek yang telah ditetapkan dengan siri pembukaan. Terdapat 8 model yang dijalankan untuk mendapatkan hasil yang tepat untuk menunjukkan kelakuan dan kekuatan keluli terbentuk sejuk. Tiang terbina terdiri daripada dua saluran keluli terbentuk sejuk yang diletakkan di belakang dan disambungkan di web menggunakan dua pengikat skru penggerudian sendiri pada jarak yang ditetapkan sepanjang tiang. Kedua-dua hujung setiap tiang akan dikimpal dengan plat keluli untuk bertindak sebagai sokongan tetap. Kajian ini membentangkan penerangan yang terperinci mengenai kajian percubaan dan teori untuk menyiasat beban maksimum dan tingkah laku lengkokan mod kegagalan bagi tiang keluli terbentuk sejuk. Mod kegagalan terbahagi kepada 4 kategori iaitu lengkokan tempatan, belitan, meleding dan lengkokan lenturan. Semua model dalam bukaan memberikan data yang berbeza. Model tanpa bukaan memberi beban maksimum lebih tinggi berbanding model dengan bukaan. Penggunaan transducer dalam ujian mampatan juga memberikan tanda awal bagaimana struktur lajur berkelakuan di bawah beban paksi.

ABSTRACT

This paper aims to determine the ultimate load of built-up C section cold-formed steel with openings compared to single C section and study the buckling behavior of built-up C section. Cold-formed steels are widely used in construction industry, manufacturing technologies and relevant standards. Cold-formed steels are widely available with difference sizes and shapes. Cold-formed steel sections are manufactured with difference process such as cold roll forming and press brake operation. In the tests, compression loading were imposed on fix ended short columns with opening series. There are total of 8 specimens was conducted as to get an accurate result to show the behavior and strength of built-up cold-formed steel. The built-up column consists of two individual cold-formed steel lipped channels placed back-to-back and connected at the web using two self-drilling screw fasteners at specified spacing along the column length. Both end of each columns will be welded with a steel plate to act as fixed support. This paper presents a detailed descriptions of an experimental and theoretical studies to investigate the maximum load and buckling behavior of cold-formed steel columns. Mode of failure split into four categories such as local buckling, distortional buckling, warping and flexural buckling. All of specimen in openings give different data. Specimen without opening give more higher maximum load compare to specimen with opening. The use of transducer in the compression test gives the earlier sign how column structures behave under axial load.

TABLE OF CONTENT

DECLARATION

TITLE PAGE

ACKNOWLEDGEMENTS **ii**

ABSTRAK **iii**

ABSTRACT **iv**

TABLE OF CONTENT **v**

LIST OF TABLES **viii**

LIST OF FIGURES **ix**

LIST OF ABBREVIATIONS **xi**

CHAPTER 1 INTRODUCTION **1**

1.1 Introduction 1

1.2 Problem Statement 3

1.3 Objective of Study 4

1.4 Scope of Study 5

1.5 Significant of Study 5

CHAPTER 2 LITERATURE REVIEW **6**

2.1 Introduction 6

2.2 Method of Forming 7

2.2.1 Cold Roll Forming 8

2.2.2 Press Brake Operation 9

2.3 Classification of Section 10

2.3.1	Built-up Section	10
2.4	Opening	10
2.5	Comparisons of Cold-Formed Steel and Hot Rolled Steel	12
2.6	The Behaviour of Cold-Formed Steel	14
2.4.1	Local Buckling	14
2.4.2	Distortional Buckling	15
2.4.3	Warping	16
2.4.4	Flexural Buckling	16
2.7	Previous Research Paper	18
2.7.1	Behaviour of Cold-Formed Steel Built-up Section	18
2.7.2	Cold-Formed Steel Built-up Section with Web Opening to Compression Loading	18
CHAPTER 3 METHODOLOGY		19
3.1	Introduction	19
3.2	Flow Chart of the Study	20
3.3	Section Parameter	21
3.4	Specimen Preparation	22
3.5	Test Setup	25
CHAPTER 4 RESULTS AND DISCUSSION		30
4.1	Introduction	30
4.2	Load versus Vertical Displacement	30
4.3	Buckling Behaviour	32
CHAPTER 5 CONCLUSION		38
5.1	Conclusion	38

5.2	Recommendation	38
	REFERENCES	40
	APPENDIX A DIMENSION FOR SPECIMEN WITH OPENINGS	44
	APPENDIX B SPECIMEN PREPARATION	47

LIST OF TABLES

Table 2.1	Comparison of Cold-Formed Steel and Hot Roll Steel	14
Table 3.1	Parameter of Built-up C Section	21
Table 4.1	Finalize of Buckling Behaviour for Each Specimen BC203-1.2	31
Table 4.2	Finalize of Buckling Behaviour for Each Specimen SC203-1.2	31
Table 4.3	Finalize of Buckling Behaviour for Each Specimen BC203-1.2	32

LIST OF FIGURES

Figure 1.1	Building composed entirely of cold formed steel sections	2
Figure 1.2	Sorts of built-up sections	4
Figure 2.1	Various shapes of Cold-Formed Steel section	7
Figure 2.2	Various shapes of Cold-Formed Steel section	7
Figure 2.3	Cold Roll Forming Machine	8
Figure 2.4	Press Braking System	9
Figure 2.5	Press Brake Operation Machine	10
Figure 2.6	Typical built-up structural sections	10
Figure 2.7	Cold-Formed steel with opening section	11
Figure 2.8	Cold formed steel	12
Figure 2.9	Hot Rolled Steel	13
Figure 2.10	Local Buckling Mode of Compression Members	15
Figure 2.11	Distortional Buckling Mode of Compression Members	16
Figure 2.12	Flexural Buckling Mode of Compression Members	17
Figure 3.1	Flow Chart of the Research	20
Figure 3.2	Typical built-up C-section	21
Figure 3.3	Label definition for Built-up C-section	22
Figure 3.4	Self Drilling Screw	23
Figure 3.5	Screw connection for the specimen	23
Figure 3.6	Typical screw spacing and layout	24
Figure 3.7	Schematic of screw spacing and layout	24
Figure 3.8	Technician welding the specimen	25
Figure 3.9	Transducers	26
Figure 3.10	Data Logger	27
Figure 3.11	The position of setup the transducer before testing	27
Figure 3.12	Schematic of test setup	28
Figure 3.13	The specimen's position of opening for section 203mm	28
Figure 3.14	Base plate that used for welded at the top and bottom of the specimen	29
Figure 3.15	Specimen welded at top and bottom support	29
Figure 4.1	Load versus vertical displacement for specimen BC 203-1.2	31
Figure 4.2	Load versus vertical displacement for specimen SC 203-1.2	32
Figure 4.3	Buckling behaviour of specimen BC 203-1.2-A1	33

Figure 4.4	Buckling behaviour of specimen BC 203-1.2-A2	33
Figure 4.5	Buckling behaviour of specimen BC 203-1.2-A3	34
Figure 4.6	Buckling behaviour of specimen BC 203-1.2-A4	34
Figure 4.7	Buckling behaviour of specimen BC 203-1.2-A5	35
Figure 4.8	Buckling behaviour of specimen BC 203-1.2-A6	35
Figure 4.9	Buckling behaviour of specimen BC 203-1.2-A7	36
Figure 4.10	Buckling behaviour of specimen BC 203-1.2-A8	36
Figure 4.11	Eight specimens for BC 203-1.2 after testing	37

LIST OF ABBREVIATIONS

CFS	Cold-Formed Steel
FE	Finite Element
FKASA	Fakulti Kejuruteraan Awam dan Sumber Alam
UTM	Universal Testing Machine
AISI	American Iron and Steel Institute
JIS	Japanese Industrial Standard
SPCC	Steel Plate Cold Rolled Common
BC	Built-up C
SC	Single C
DB	Distortional Bottom
DBB	Distortional Bottom Back
DTB	Distortional Top Bottom
DTF	Distortional Top Front
DMB	Distortional Middle Back
DMF	Distortional Middle Front
LM	Local Middle
LT	Local Top
LBF	Local Bottom Front
LBW	Local Bottom Web
LTF	Local Top Front
WBB	Web Bottom Back
WBF	Web Bottom Front
WMF	Web Middle Front

CHAPTER 1

INTRODUCTION

1.1 Introduction

Cold-formed steel has been recently brought into Malaysia construction. The use of this structures is expanding quickly around the world due to the many approach in construction and manufacturing technologies and relevant standards. It is a steelwork innovation that has high potential to be developed in Malaysia, that can offer advantages such as fast erection, lightness of weight, clean and easier construction. Cold-formed steel structure is widely available with difference sizes and shape. Cold-formed steel members usually have symmetrical cross-sections, higher of strength and better resistance out-of-plane resistance.

In addition, cold-formed steel is a steel product that is formed by a steel strip or sheet of uniform thickness, in cold state. It is regarded as steel strip with uniform profile along its length and it is usually used in load bearing application. The use of cold-formed steel section can be found in automobile industry, shipbuilding, rail transport and construction industry. In building construction, the cold-formed steel is utilised in both structural and non-structural. As non-structural members, the advantages are more on rust resistance and aesthetic purposes. Figure 1.1 shows the building that used cold-formed steel sections. Cold-formed steel is a thin walled section and it is available with different sizes and shapes. It provided with holes to accommodate plumbing, electrical, and heating conduits in the walls and ceilings of buildings. The thicknesses of material for thin wall sections usually range from 0.373 mm to 6.35 mm. One of the best ways to perform this study is to connect two single members together to form a built-up I section.



Figure 1.1 Building composed entirely of cold-formed steel sections

Source: (Specifying cold-formed steel to meet project goals - Construction Specifier, 2017)

Next, for built-up section, it has symmetric cross sections, higher strength and better resistance against out-of-plane. It is easily failed in overall buckling, if not laterally supported. A built-up section can spend more distance, higher torsional; stiffness and higher load bearing capacity. Therefore, the use of built-up sections can be a major advantage of economic since the whole manufacture process remains the same. When structure section modified with opening, it will be represented in thin-walled structural members to facilitate access for services and inspection. It will obviously result in changes in stress distribution within the member. A reduction of strength and variations in the buckling characteristics of the plate elements.

In building construction, there are primarily two types of structural members: hot rolled steel shapes and cold rolled steel shapes. Cold-formed steel shapes are formed at room temperature while hot rolled steel shapes are formed at elevated temperatures. Cold-formed steels are made from structural quality sheet steel and formed into shape, either

through press braking blanks sheared from sheet or coils by rolling forming the steel through a series of dies. Due to the relative method of manufacturing process, a large number of different compositions can be produces to fit the demands of optimized for both structural and economical purposes.

1.2 Problem Statement

Cold-formed steel can be productive in many applications where conventional hot rolled steel proves uneconomic. Cold-formed steel is a thinner material compared to the other type of hot rolled steel. The buckling stability will be different compared to conventional structural steel. When it is thin and lightweight, the strength not strong than hot rolled steel. Effect strength of cold-formed steel due to position of opening also need to be taken because the difference behaviour of failure mode occurs when different position of opening. Next, the stiffener is commonly used in cold-formed steel section to provide a continuous support along a longitudinal edge of flange to increase the buckling stress. It can be easily brake pressed on the free edge of an unstiffened plate. Further, the stiffeners also may transform considerably their distortional buckling, post buckling and collapse behaviour.

In most past researches, cold-formed steel built-up sections as cold-formed C face-to-face (Figure 1.2(a)) and nested section (Figure 1.2(c)), were studied. In building construction, cold-formed steel C back-to-back sections (Figure 1.2(b)) were applied. However, there are few researches on this type of built-up section. Since the torsional is much smaller than the C face-to-face section, more detailed investigation on buckling behaviour of the C back-to-back section is needed.

REFERENCES

El Aghoury, M. A., Hanna, M. T. and Amoush, E. A. 2017 Experimental and theoretical investigation of cold-formed single lipped sigma columns, *Thin-Walled Structures*. Elsevier, 111(April 2016), 80–92. doi: 10.1016/j.tws.2016.10.025.

Built-Up Sections _ Civil Engineering 2019.

ClarkDietrich Building Systems 2017. Available at: <http://www.clarkdietrich.com/>.

Crisan, A., Ungureanu, V. and Dubina, D. 2012 Behaviour of cold-formed steel perforated sections in compression. Part 1 - Experimental investigations, *Thin-Walled Structures*. Elsevier, 61, 86–96. doi: 10.1016/j.tws.2012.07.016.

Fratamico, David C. Torabian, Shahabeddin Zhao, Xi Rasmussen, Kim J.R. Schafer, Benjamin W. 2018 Experimental study on the composite action in sheathed and bare built-up cold-formed steel columns, *Thin-Walled Structures*. Elsevier Ltd, 127(January), 290–305. doi: 10.1016/j.tws.2018.02.002.

Georgieva, I. Schueremans, L. Vandewalle, L. Pyl, L. 2012 Design of built-up cold-formed steel columns according to the direct strength method, *Procedia Engineering*, 40, 119–124. doi: 10.1016/j.proeng.2012.07.066.

Haidarali, M. R. and Nethercot, D. A. 2012 Local and distortional buckling of cold-formed steel beams with edge-stiffened flanges, *Journal of Constructional Steel Research*. Elsevier Ltd, 73, 31–42. doi: 10.1016/j.jcsr.2012.01.006.

Kang, K. 2017 Investigation on Flexural Behavior of Cold-Formed Steel C Back-To-Back Beams By Academic Year 2017 Investigation on Flexural Behavior of Cold-Formed Steel C Back-To-Back Beams.

Kang, T. H.-K., Biggs, K. A. and Ramseyer, C. 2013 Buckling Modes of Cold-Formed Steel Columns, *International Journal of Engineering and Technology*, 5(4), 477–451. doi: 10.7763/ijet.2014.v5.594.

Kulatunga, M. P. Macdonald, M. Rhodes, J. Harrison, D. K. 2014 Load capacity of cold-formed column members of lipped channel cross-section with perforations subjected to compression loading - Part I: FE simulation and test results, *Thin-Walled Structures*. Elsevier, 80, 1–12. doi: 10.1016/j.tws.2014.02.017.

Kulatunga, M. P. and Macdonald, M. 2013 Investigation of cold-formed steel structural members with perforations of different arrangements subjected to compression loading, *Thin-Walled Structures*. Elsevier, 67, 78–87. doi: 10.1016/j.tws.2013.02.014.

Meiyalagan, M., Anbarasu, M. and Sukumar, S. 2010 Investigation on Cold - formed C - section Long Column with Intermediate Stiffener & Corner Lips – Under Axial Compression, *International Journal of Applied Engineering Research*, Dindigul, 1(1), 28–41.

Mulligan, G. P. and Pekoz, T. 2008 Locally Buckled Thin-Walled Columns, *Journal of Structural Engineering*, 110(11), 2635–2654. doi: 10.1061/(asce)0733-9445(1984)110:11(2635).

National Material Steel Group 2019 The Differences Between Hot and Cold Rolled Steel _ National Material Company - Steel Processing Facilities.

Prakash, Parvati S Samuel, J Joanna, P S Sakaria, P Eapen 2014 Flexural Behavior of Cold Formed Steel Beams with end Stiffeners and Encased Web, 3(11), 1276–1279.

Brockenbrough, R. L. 2000 Section 10 Cold-Formed Steel Design, *Design*, 1–46.

Ranawaka, T. 2016 Distortional Buckling Behaviour of Cold-Formed Steel Compression Members At Elevated Temperature.

Reddy, S., R, V. K. M. and Sankh, P. A. C. 2016 An Experimental and Analytical study of Cold-formed Steel Structural Members with Perforations Subjected to Compression Loading, 4(2), 689–696.

Reliance Foundry 2017 Hot Rolled vs Cold Rolled Steel | Metal Casting Blog. Available at: <http://www.reliance-foundry.com/blog/hot-vs-cold-rolled-steel#gref>.

Sadovský, Z. Kriváček, J. Ivančo, V. Ďuricová, A. 2012 Buckling strength of lipped channel column with local/distortional interactions, *Procedia Engineering*, 40, 399–404. doi: 10.1016/j.proeng.2012.07.115.

Setiyawan, P. 2015 Cold-Formed Steel Technology in Building Structure and its Problems as an Alternative Solution of Corrosion Resistant Structures at Coastal Areas, *International Conference on Coastal and Delta Areas*, 1(1), 263–272. Available at: <http://jurnal.unissula.ac.id/index.php/ICCDA/article/view/633/562>.

Shanmugam, N. E. 2002 Openings in Thin-Walled steel structures, *Thin-Walled Structures*, 28(3–4), 355–372. doi: 10.1016/s0263-8231(97)00053-0.

Shanmugam, N. E. and Dhanalakshmi, M. 2001 Design for openings in cold-formed steel channel stub columns, *Thin-Walled Structures*, 39(12), 961–981. doi: 10.1016/S0263-8231(01)00045-3.

Shanmugam, N. E., Thevendran, V. and Tan, Y. H. 1999 Design formula for axially compressed perforated plates, *Thin-Walled Structures*, 34(1), 1–20. doi: 10.1016/S0263-8231(98)00052-4.

Specifying cold-formed steel to meet project goals - Construction Specifier 2017.

Stone, T. A. and LaBoube, R. A. 2005 Behavior of cold-formed steel built-up I-sections, *Thin-Walled Structures*, 43(12), 1805–1817. doi: 10.1016/j.tws.2005.09.001.

Structures, C. and Ii, F. 2008 Cold-Formed (CF) Structures, (February), pp. 18–20.

Swanton Welding Company Inc. 2017 Hot Rolled Steel vs. Cold Rolled Steel. Available at: <https://swantonweld.com/hot-rolled-steel-vs-cold-rolled-steel/>.

West Memphis Steel 2019 Brake Press - West Memphis Steel.

Whittle, J. and Ramseyer, C. 2009 Buckling capacities of axially loaded, cold-formed, built-up C-channels, *Thin-Walled Structures*, 47(2), 190–201. doi: 10.1016/j.tws.2008.05.014.

Yu, W., Ph, D. and Wiley, J. 2000 Steel Design Third Edition, New York.

Yu, W. W. and LaBoube, R. A. 2010 Cold-Formed Steel Design: Fourth Edition, Cold-Formed Steel Design: Fourth Edition. doi: 10.1002/9780470949825.